

Ezi-lift

PRODUCTS (AUST)

SALES·SERVICE·HIRE·PARTS

P: 1300 394 543 E: sales@ezi-lift.com.au W: www.ezi-lift.com.au



FEATURES:-

- Level in Mast – Ensures mast is vertical before operation.
- Telescoping Legs – For uneven surfaces, stairways, slopes etc.
- Telescoping Mast – Compact, Strong and Light – made with robust, specially heat-treated aluminium.
- Electric Motor – Variable speed controller with long cable and belt clip.
- Manual Controls – If no mains power available, use electric drill or handle to wind lifter.
- Emergency Stop Button – Also used to switch to manual control.
- Setup in 30 seconds – No tools required.
- Overload Cut-Out – Fitted with overload clutch for safety.
- Retractable Legs – Lift loads adjacent to wall.
- Fine Positioning – Align load precisely with variable speed controller.

Model	Basic Height	Lifting Height	Load Capacity	Weight		Dimensions	
				Lifter	Platform	Stowed	Operating
CM-340	970 mm	3.3 m	130kg-3.0m 120kg-3.3m	21kg	5.3kg	300x300mm	1x1.1m
CM-520	1190 mm	4.9 m	140kg-3.0m 130kg-4.0m 90kg-4.9m	38kg	5.3kg	380x380mm	1.5x1.4m



Adjustable legs allow for infinite adjustment



Simple push button design



Mast level indicator



Variable speed controller

