Up-Lift

UG Series

Sliding Rail Man Lifts

Designed with advanced technical input and with a special focus on quality and operator safety requirements, Up-Lift UG series personnel lifts are compact, with superior outer finishes, light and easy to handle and have many safety features.

Employing the traditional sliding rail mast design, UG personnel lifts use high quality parts, with critical components being sourced from world leading suppliers. The special attention given to practical features and safety standards has created a range of machines with greater stability and safety by comparison with other similar portable man lifts models.

<u>Key features of the UG model:</u>

1/ Powers supply indication, outrigger indication lights and back-up power for AC modes
2/ Ergonomically designed cage
3/ Extruded aluminium outriggers are stored on the side below the top of the machine, keeping the stored height to a minimum
4/ Designed to allow passage through standard doorways, lifts and elevators. Mobility for higher models are enhanced with tilt-back support system
5/ Critical push button controls are all accessible directly from the platform.
6/ Both AC and DC options available
7/ High strength and high durability aluminium aircraft materials greatly reduce weight and enhances the stability of the machine
8/ High quality fully retractable imported spiral cable ensures strongly reliable aerial operation.

MODEL	UG16	UG20	UG25	UG30	UG35	UG38	UG40
Max Platform Height (m)	4.7	6.1	7.5	8.8	10.3	11.7	12.3
Max Working Height (m)	6.7	8.1	9.5	10.8	12.3	13.7	14.3
Rated Load (kg)	159	159	159	159	136	136	136
Stored Dimensions (m)	1.22×0.80 ×1.78	1.22×0.80 ×1.78	1.28×0.80 ×1.98	1.34×0.74 ×1.98	1.40×0.80 ×1.98	1.47×0.80 ×1.98	1.42×0.80 ×2.80
Tilted Dimensions (m)	N/A	N/A	N/A	N/A	N/A	N/A	2.85x0.80 x1.98
Platform Dimension (m)	0.68×0.66 ×1.10	0.68×0.66 ×1.10	0.68×0.66 ×1.10	0.68×0.66 ×1.10	0.68×0.66 ×1.10	0.68×0.66 ×1.10	0.68×0.66 ×1.10
Outriggers Foot-Print (m)	1.55x1.75	1.55x1.75	1.55x1.75	1.55x1.75	2.06x2.26	2.34x2.70	2.33x2.58
Wall Access Distance (m)	0.12	0.12	0.12	0.12	0.36	0.53	0.53
Voltage AC/DC Model (v)	230/12	230/12	230/12	230/12	230/12	230/12	230/12
Total Weight AC/DC Model (kg)	315/357	340/382	360/402	380/422	415/457	455/487	480/550
Power Rating (kW)	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6